

Workwear World

Safety footwear: standards and changes to basic requirements

Standards for PPE products are regularly reviewed and adapted when necessary. This is also the case for DIN EN ISO 20345, which defines the requirements for safety footwear. In order for a pair of shoes to be designated as safety footwear and given the SB symbol, they must meet the following basic requirements:

- Minimum requirements for the toe cap:
 - Drop test at 200 joules of test energy (20 kg from a height of approx. one metre)
 - Static pressure test at 15 kiloNewtons (approx. 1,500 kg of pressure)
 - Inside length depending on shoe size (e.g. 39 mm in sizes 41-42)
 - Corrosion resistance for steel toe caps, behaviour test for plastic toe caps when exposed to heat and chemicals
- Resistance, non-toxicity and properties of the materials used in the sole and shoe upper
- Height, ergonomics and comfort of the shoe

In addition to the above-mentioned requirements, **another basic requirement** has now been added:

Slip resistance on floor tiles with a sodium lauryl sulphate solution (NaLS), a type of soap solution. The symbol 'Ø' is used if the test cannot be carried out, for example because the shoe has metal spikes.

What additional requirements does EN ISO 20345:2022 now specify?

Alongside the basic requirements for safety footwear, there are additional requirements and provisions for various workplace hazards. Changes were also made here when the standard was revised during the second quarter of 2022.

Slip resistance

The **slip resistance test procedure** for safety footwear and the corresponding certification have been changed. The previous certifications 'SRA', 'SRB' and 'SRC' will no longer be used; instead, the **certification 'SR' will now be used** if the shoe passes a slip resistance test on a ceramic tile with glycerine. In addition to the flooring used to carry out the test, the test procedure has also been modified.

Penetration resistance

The term 'penetration resistance' for describing safety footwear will now be replaced by the phrase '**puncture resistance**'. The puncture resistance test will now be carried out on the basis of ISO 22568-3 and ISO 22568-4 instead of EN 12568.

New symbols for the certification of safety footwear for puncture resistance have also now been added:

Symbol	Description
P	<ul style="list-style-type: none"> For steel soles At least 1,100 Newtons of pressure Tested with 4.5 mm nail
PL	<ul style="list-style-type: none"> For non-metallic soles With 1,100 Newtons of pressure Tested with 4.5 mm nail
PS	<ul style="list-style-type: none"> For non-metallic soles Average value of four tests must not be lower than 1,100 Newtons Tested with 3.0 mm nail

Resistance to oil and petrol

Resistance to oil and petrol is no longer included in protection classes S1 to S5. Instead, the special **symbol FO** will now be used.

Water penetration and absorption of the shoe upper material

The additional requirement WRU (water-resistant uppers), which describes the water-repellent effect of the shoe's upper, has been changed to **WPA**.

Additional protection classes

Protection classes S6 and S7 have been added. These certify shoes that also include a waterproof feature, e.g. a membrane:

Short codes for footwear made from leather and other materials, excluding all-rubber or all-polymeric footwear

Symbol	Requirements	SB	S1	S2	S3	S3L	S3S	S6	S7	S7L	S7S
-	Basic requirements	X	X	X	X	X	X	X	X	X	X
-	Slip resistance on ceramic tile floors with SLS	X	X	X	X	X	X	X	X	X	X
Ø	Slip resistance not tested (e.g. shoes with metal spikes)										
-	Closed seam region	○	X	X	X	X	X	X	X	X	X
A	Antistatic footwear	○	X	X	X	X	X	X	X	X	X
E	Energy absorption of seat region	○	X	X	X	X	X	X	X	X	X
WPA	Water penetration and absorption	○	○	X	X	X	X	X	X	X	X
WR	Water resistance	○	○	○	○	○	○	X	X	X	X
P	Perforation resistance: metal insert	○	○	○	X	-	-	○	X	-	-
PL	Perforation resistance: non-metal insert, 4,5 mm nail	○	○	○	-	X	-	○	-	X	-
PS	Perforation resistance: non-metal insert, 3,0 mm nail	○	○	○	-	-	X	○	-	-	X
-	Cleated outsole	○	○	○	X	X	X	○	X	X	X

X = mandatory, ○ = optional, - = not necessary/possible

New additional requirements

With regard to slip resistance, overcaps and ladder grip, optional additional requirements have been introduced.

- **Scuff cap (SC):** In order to determine abrasion on the overcap, a Martindale abrasion test of 8,000 cycles will be carried out. According to the test, the overcap must not develop any holes across its entire thickness.
- **Slip resistance (SR):** This new additional requirement tests the slip resistance of the safety shoes on ceramic tiles with glycerine. When the heel slides forward, a coefficient of friction of ≥ 0.19 mm is allowed. When the front part of the shoe slides backwards, a coefficient of friction of ≥ 0.22 mm is allowed.
- **Ladder grip (LG):** To offer better grip on ladders, the outsole of a safety shoe must have a transverse profile with a height of at least 1.5 mm in the ankle area.

Overview of all additional requirements:

Symbol	Meaning	Description	Note
P	Perforation Resistance, Steel Midsole	Perforation resistance	Changed
PL	Perforation Resistance, Non-metallic Midsole, Large Nail		New
PS	Perforation Resistance, Non-metallic Midsole, Small Nail		New
C	Conductivity	Conductivity	
A	Antistatic	Antistatic properties	
HI	Heat Insulation	Heat insulation	
CI	Cold Insulation	Cold insulation	
E	Energy Absorption	Energy absorption	

WR	Water Resistance	Water resistance	
M	Metatarsal Protection	Metatarsal protection	
AN	Ankle Protection	Ankle protection	
CR	Cut Resistance	Cut resistance	
SC	Scuff Cap	Scuff cap	New
SR	Slip Resistance	Slip resistance on ceramic tiles / glycerine	New
WPA	Water Penetration & Absorption	Water penetration and absorption	Changed
HRO	Heat Resistance Outsole	Resistance to contact heat	
FO	Resistance to Fuel and Oil	Fuel/oil resistance	
LG	Ladder Grip	Ladder grip	New